TSS 8807



## PRODUCT DATA SHEET

### **Product Description**

**StuccoStar** is a ready-made filler for interior use on most building surfaces, including timber. It provides an even, smooth surface for painting. StuccoStar enables the artisan to patch up and touch up interior surfaces, both old and new, preparing it for painting and fills joints and hairline cracks equally well. StuccoStar is superior to the conventional fillers due its plastic properties, no flaking, and high retention of adhesion and permanence.

StuccoStar bonds extremely well to all common building surfaces including gypsum, gypsum boards, spray plasters, cementitious materials, wood, and galvanized steel laths. StuccoStar is used as a thin coat filler where spray plaster cannot be used. It also goes into patching of hairline cracks in walls, ceilings, repairs of damaged plaster work, paint work, filling of defects, nails holes in woodwork, integrity over lintels and beams, and along the top of skirtings etc.

### **Method of Application**

**Preparation:** The application surface should not have any foreign matter, dust, dirt or flaking or such surfaces should be cleaned thoroughly and StarBond Penetrating Primer or StarBond Ultra user before patching with StuccoStar. Ridges and form oil must also be removed. Surfaces with encroaching dampness should damproofed before applying this filler. If dampness is a constant condition, then use of Star Acrylic Filler is advised. Old painted surfaces should be first washed with soda and water solution, rinsed, and dried before filling.

**Application:** Initial application should be a thin even layer; if the area to be repaired requires a thick coat, apply several thin layers. Each layer has to dry before the next layer is added. Within 24 hours of application, sandpaper lightly over the dry final surface before painting.

Tools and equipment should always be cleaned out with water to ensure smooth re-use.

### Health & Safety

Prolonged contact with eyes and skin is not recommended. Always wear protective eye-gear and overalls. Avoid any ingestion. Detailed information is given in the MSDS.

### Packing & Storage

StuccoStar is supplied in 5kg and 20kg plastic pails.

Store in a clean, dry place. Always avoid completely direct sunlight and extremes of heat and cold, especially frost. As long as the containers remain sealed, usage up to 12 months is possible. Always follow first-in-first-out policy.



**TSS 8807** 

# **PRODUCT DATA SHEET**

Product	StuccoStar Ready-mixed quick drying filler of fine inert extenders
Binder	Acrylic copolymer
Fillers	Finely- graded marble
Dilution	With water if required
Colour	White
Shrinkage	Minimal
Density	1.75
Consumption	6 - 8 m²/litre on average
Application	Manual using spatula
Storage	12 months in sealed original container
Packing	5kg and 20kg plastic pails

### **Product Technical Data**

TRIMIX offers a complete range of products for spray plastering and all-surface finishing.

Technical Service is offered by Trimix LLC's Technical Service Department (TSD). A team of Sales/Demonstration Instructors is always available for technical assistance to the Customers on the correct usage of our products. The information given in this leaflet is based on laboratory research as well as extensive field work and application and its present state of knowledge and intended to provide general information on the products and methods of usage. All products are subject to standard conditions of sale which are available on request. Prospective users are advised to determine the suitability of the products and suggestions before adopting them on a commercial scale. Trimix is not liable for any incidental or consequential damages directly or indirectly sustained nor for any loss caused by application of the product(s) not in accordance with instructions or for other than their intended use. Any claim shall be deemed waived unless made in writing to us with 15 days from the date it was or reasonably should have been discovered.

