



TILESTAR

Tile Paste

TTP 8804

PRODUCT DATA SHEET

Product Description

TileStar TilePaste is a ready-to-use, all purpose acrylic adhesive for tiles and clinkers, formulated and prepared for exterior and interior surfaces of concrete, plasterboard, gypsum, etc. Application is easy using notched trowel. This special formulation used fine-grain crushed dolomite and acrylic binder with proprietary additives to improve plasticity and adhesion. This product has anti-fungal properties from the additives in it.

Preparation & Application

Preparation: Level the surface, remove all resultant dust and dirt by abrasion and brushing. Surface for application should be free from salts, oil, greases and ridges and not damp. Hollows, cracks, chips, and damages should be restituted with recommended fillers. Likewise, absorbent or porous surfaces and plasterboards should be restituted.

Application: Using the smooth side of the notched trowel apply TileStar TilePaste in a 3mm layer on the surface. Care should be taken that the application should be only for an area where the laying of the tiles can be completed within 15 minutes. Also, formation of 'skin' over the applied paste should be avoided. In any case, the placement of the tiles should be done before the applied paste becomes surface dry. Drag the notched edge of the trowel through the applied layer, then place, press, and manoeuvre the tiles flush to ensure complete adhesion. All overflow of the adhesive around and over the tile should be cleaned before it dries using a wet sponge. Provision for expansion joints should be done at the design stage.

All tools to be washed with water and wiped dry before storing for easy reuse.

Health & Safety

Prolonged contact with eyes and skin is not recommended. Always wear protective eye-gear and overalls. Detailed information is given in the MSDS. Affected areas should be washed with plain water immediately; seek medical attention if necessary.

Packing & Storage

TileStar TilePaste is supplied in 5kg and 25kg plastic pails.

Store in a clean, dry place. Always avoid direct sunlight and extremes of heat and cold.

Lid should be closed tightly after use. If stored unopened in good condition, product will have a shelf life of 6 months. Always follow first-in-first-out policy.





TILESTAR

Tile Paste

TTP 8804

PRODUCT DATA SHEET

Product Technical Data

Product	TileStar TilePaste Premixed
Fillers	Precisely-graded crushed limestone
Binder	Acrylic
Toxicity	Non-toxic
Temperature Resistance	Not affected by frost. Withstands a max of 120°C
Consumption	1.5-3kg/m ² /1mm thickness depending on surface conditions
Storage	6 months in original, unopened condition
Packaging	5kg and 25kg plastic pail

TRIMIX offers a complete range of products for spray plastering and all-surface finishing.

Technical Service is offered by Trimix LLC's Technical Service Department (TSD). A team of Sales/Demonstration Instructors is always available for technical assistance to the Customers on the correct usage of our products. The information given in this leaflet is based on laboratory research as well as extensive field work and application and its present state of knowledge and intended to provide general information on the products and methods of usage. All products are subject to standard conditions of sale which are available on request. Prospective users are advised to determine the suitability of the products and suggestions before adopting them on a commercial scale. Trimix is not liable for any incidental or consequential damages directly or indirectly sustained nor for any loss caused by application of the product(s) not in accordance with instructions or for other than their intended use. Any claim shall be deemed waived unless made in writing to us with 15 days from the date it was or reasonably should have been discovered.

